

NEW
FROM E-Z TAPING SYSTEM!

e-z 

**FLAME FIGHTER
FIRE CAULK**

From the makers of E-Z Fire Tape®



FLAME FIGHTER FIRE CAULK

COMMERCIAL INTUMESCENT FIRE CAULK



PRODUCT FEATURES

- NON-TOXIC
- NON-CORROSIVE
- ENVIRONMENTALLY SAFE
- UNAFFECTED BY FREEZE/THAW
- EASY GUNABILITY
- WATER RESISTANT
- ADHERES TO MOST MATERIALS
- PAINTABLE/SANDABLE
- EASY GUNABILITY
- WATER RESISTANT
- ADHERES TO MOST MATERIALS
- PAINTABLE/SANDABLE

Factory Ratings

3000° F FOR 8 HOURS
ASTM-E84 0 FLAME/0 SMOKE
ASTM-E136 NON-COMBUSTIBLE
ASTM-E119 COMPATIBLE
ASTM-E814 COMPATIBLE



CAULKING AND SEALANTS SURFACE BURNING CHARACTERISTICS

FLAME SPREAD 0

SMOKE SPREAD 0

61RF

ALSO CLASSIFIED IN ACCORDANCE WITH ASTM-E136 (CURRENT EDITION), "STANDARD TEST METHOD FOR THE BEHAVIOR OF MATERIALS IN A VERTICAL FURNACE AT 750°C."

SEE UL BUILDING MATERIALS DIRECTORY

Phone: 800.721.8273 • Email: info@e-ztape.com • www.e-ztape.com